

BODY SPECIFICATIONS

Body Capacity	20yd³
A. Body Length	242"
B. Height Of Body Above Chassis	95"
C. Body Width	96"
D. Hopper Opening Width	78"
E. Hopper Opening Height	66"
F. Loading Sill Below Chassis Frame	-2"
G. Height Of Tailgate Above Chassis Frame (Tailgate Raised)	182"
Hopper Capacity	2.8yd ³
Hopper Capacity with CLD	3.1yd³
Dynamic Hopper Capacity (yd³/minute)	6.7yd³
Body Weight	13,500 LBS.



MINIMUM CHASSIS REQUIREMENTS

	Conventional Chassis	Cabover Chassis
Recommended Minimum GVWR	12,000 LBS.	20,000 LBS.
Recommended Front Axle	23,000 LBS.	23,000 LBS.
Recommended Rear Axle	30,000 LBS.	30,000 LBS.
Recommended Rear Suspension Rating	14,000 LBS.	14,000 LBS.
Recommended Drop Axle Rating	49,000 LBS.	57,000 LBS.
CA Cab to Drive Axle	148"	148"
Estimated Wheelbase	216"	176"
CF Minimum to End of Frame	171"	171"



Body Construction

- Body Sides: 10 Gauge GR80
- Body Roof: 10 Gauge GR80
- Body Floor: 10 Gauge GR80
- Ejection Panel: 10 Gauge GR80
- Sweep Face: 3/16 GR100
- Tailgate Side Wall: 10 Gauge GR80 Upper, 7 Gauge GR50 Lower
- Tailgate Floor: 3/16 GR100

Features

- High Strength Curved Shell Body
- Auto Back-Pack
- **Engine Accelerator**
- Reservoir Sight Gauge
- Chrome Cylinder Rods
- 30" x 34" Access Door (Street Side)
- Backup Alarm
- Driver Alert Buzzer (Curbside)
- High-Mount Rear Light Bar
- Work Lights
- LED ANSI/DOT Lighting
- 12 Month Body Warranty
- 24 Month Cylinder Warranty
- Pack Cycle Time of 20-24 Seconds

Hydraulics

- Oil Reservoir: 50 Gal.
- Oil Flow w/ Standard Pump: 36 **GPM**
- Operating Pressure: 2,500 PSI
- Hose Burst Ratio: 4 to 1
- Return Filter: 10 Micron
- Pack Cylinders: 4.5"
- Sweep Cylinders: 4.5"
 - **Eject Cylinders** • 20yd3: 5.25", 2 Stage Telescopic
- Tailgate Lift: 3.5"

Optional Features

- · Container Roll Bar with Lip-and-Latch
- · 12,000 LBS. Reeving Winch
- 8,000 LBS. or 12,000 LBS. Overhead Drum Winch
- Single & Dual Tipper(s)
- Cart Tipper Tap-In-Kits
- Work Lights
- Strobe Lights
- Broom and Shovel Holder
- Rear View Color Camera System
- Hopper Bottom AR400



701 PERFORMANCE DRIVE | CEDAR FALLS, IA 50613 PHONE: (319) 266-1721 | FAX: (319) 266-8207